

FAT-134 Optical Fiber Distribution Box Specifications

Version:1.0









Download CN ver

FAT-134 type fiber optic distribution box specifications

FAT-134 type optical fiber distribution box is used in the terminal access link of FTTH optical fiber to the access system. It is an ideal supporting equipment for wiring between optical nodes and terminal equipment in optical fiber transmission networks. It has the ability to support optical fiber storage, It has the function of flexible scheduling of light splitting and wiring. The protection level of this product reaches IP68, and is suitable for outdoor pole and wall-mounted installation. The maximum capacity 288 core, it can hold one uncut cable, 11pcs branch cables, and use an optical fiber quick connector to drop cable.













Reliable sealing

The input and output cable ports are sealed with silicone sealing rings. the cable ports are tightened by the nut screws, the sealing performance will be better.




Optical fiber splicing trays and storage tray adopt a friendly modular structure design. The number of splicing trays can be increased or reduced according to capacity to meet the needs of different users. Supports coiled storage of optical fibers with loose tubes, and the bending radius of the optical fiber is greater than 30 mm.



Powerful Features

Supports splicing, splitting, wiring, branching, pass-through inventory of optical cables.

Supports wall-mounting and pole-mounting. Through the grounding device and grounding wire, the metal parts inside the distribution box are supported to be grounded.




Excellent practicabilit


The fiber distribution box shell is made of modified PP +GF material, and the internal metal parts are made of high-quality steel plate materials. It can meet the service life of more than 20 years (depending on the environment), and has good impact resistance and resistance. Corrosion properties.


To the future together


FAT-134 type fiber optic distribution box specifications














Product specifications		
Maximum capacity	288 cores	
Capacity of each splice tray	24 core/tray	
Maximum number of splice trays	max 12 pcs	
Number of optical cable entrance and exit tubes	1 oval port 11 branch ports	

Ordering Guide

Accessories information



Product number FAT-134



Product size 395*217*143mm



Product weight 2.93kg



Qty/CTN 4 set



Inner carton size 420*240*160mm



Fax: +86-(0)574-62498298

Outer carton size 460*520*340mm

Standard accessories			
1.Nylon tie		4.Wall mounting kit	1111
2. Heat shrinkable protective sleeve		5 .Metal parts	
3.Number paper	123456789888 123456789888	6 .Plastic	

To the future together.



www.ztong.com



info@ztong.com



Tel:86-0574-62498928



Ningbo Zhantong Telecom Equipment Co.,Ltd.



Fumin Industrial Zone, Moushan, Yuyao City, Zhejiang, China