


FAT-141 Optical Fiber Distribution Box Specifications

Version:1.0



View website




Download CN ver

FAT-141 type fiber optic distribution box specifications

FAT-141 type optical fiber distribution box is used in the terminal access link of FTTH optical fiber to the access system. It is an ideal supporting equipment for wiring between optical nodes and terminal equipment in optical fiber transmission networks. It has the ability to support optical fiber storage. It has the function of flexible scheduling of light splitting and wiring. The protection level of this product reaches IP65, and is suitable for outdoor pole and wall-mounted installation. You can install 3 pcs 3 : 8 PLC miniature splitters as needed. The maximum capacity 24 core, it can hold one oval cable, four branch cables, and a maximum of 16 drop cables. If necessary, you can also install 24 LC adapters, and use fiber optic quick connectors to drop cables.




Reliable sealing



The input and output cable ports are sealed with silicone sealing rings. The cable ports are tightened by the nut screws, the sealing performance will be better.

Modular design



Optical fiber splicing tray adopt a friendly modular structure design. Supports coiled storage of optical fibers with loose tubes, and the bending radius of the optical fiber is greater than 40 mm.

Powerful Features



Supports splicing, splitting, wiring, branching, pass-through inventory of optical cables.
Supports pole-mounting and wall-mounting installation.
Through the grounding device and grounding wire, the metal parts inside the distribution box are supported to be grounded.

Excellent practicability

The fiber distribution box shell is made of modified PC + ABS material, and the internal metal parts are made of high-quality steel plate materials. It can meet the service life of more than 20 years (depending on the environment), and has good impact resistance and resistance, corrosion properties.



FAT-141 type fiber optic distribution box specifications










Product specifications

Maximum capacity	24 cores
Capacity of each splice tray	24 core/tray
Maximum number of splice trays	max 1 pcs
Number of optical cable entrance and exit tubes	1 oval port, 4 branch ports, 16 drop cable ports

Ordering Guide

Accessories information

	Product number FAT-141
	Product size 293*221*113mm
	Product weight 1.4kg
	Qty/CTN 10 set
	Inner carton size 300*220*130mm
	Outer carton size 670*310*480mm

Standard accessories			
1. Nylon tie		4. Wall mounting kit	
2. Heat shrinkable protective sleeve		5. Key	
3. Number paper		6. Hose clamps	

To the future together.

 www.ztong.com

 info@ztong.com

 Tel:86-0574-62498928

 Ningbo Zhantong Telecom Equipment Co.,Ltd.

 Fumin Industrial Zone,Moushan,Yuyao City,Zhejiang,China